

# Measuring water infiltration rates

By Michael Dukes, Grady Miller and Justin Gregory

Infiltration is the process by which water enters the soil from its surface. This process affects surface runoff, soil erosion, and groundwater recharge. Being able to measure infiltration rate may be beneficial in designing sports field maintenance strategies.

The double-ring infiltrometer is the instrument most often used for measuring infiltration rates. Infiltrometers are often constructed from thin walled steel pipe with the inner and outer cylinder diameters being 8 and 12 inches, respectively; however, other diameters may be used.

A ring infiltrometer consists of a single metal cylinder that is driven partially into the soil. The ring is filled with water, and the rate at which the water moves into the soil is measured. This rate becomes constant when the soil becomes saturated.

The size of the cylinder is one source of error. A 6-inch diameter ring produces measurement errors of approximately 30%, while a 20-inch diameter ring produces measurement errors of approximately 20% compared to the infiltration rate that would be measured with a ring of an infinite diameter. It has been suggested that a diameter of at least 40 inches should be used for accurate results. However, cylinders of this size become very difficult to use in practice on light soils, because large volumes of water are required to conduct tests on sandy soils with high infiltration rates.



Photograph of 12-inch diameter (inner) and 24 inch diameter (outer) double ring infiltrometer (left/A); 6-inch diameter (inner) and 12 inch diameter (outer) double ring infiltrometer (center/B), and Mariotte siphon developed to maintain a constant inner head in the infiltration rings (right/C).

Single ring infiltrometers overestimate vertical infiltration rates. This has been attributed to the fact that the flow of water beneath the cylinder is not purely vertical. Double ring infiltrometers minimize the error associated with the single ring method because the water level in the outer ring forces vertical infiltration of water in the inner ring.

Another possible source of error occurs when driving the ring into the ground, as there can be a poor connection between the ring wall and the



## ANOTHER POSSIBLE SOURCE OF ERROR OCCURS WHEN DRIVING THE RING INTO THE GROUND, AS THERE CAN BE A POOR CONNECTION BETWEEN THE RING WALL AND THE SOIL.

soil. This poor connection can cause a leakage of water along the ring wall and an overestimation of the infiltration rate. Placing a larger concentric ring around the inner ring and keeping this outer ring filled with water so that the water levels in both rings are approximately the same reduces this error.

There are two operational techniques used with the double ring infiltrometer for measuring the flow of water into the ground. In the constant head test, the water level in the inner ring is maintained at a fixed level and the volume of water used to maintain this level is measured. In the falling head test, the time that the water level takes to decrease in the inner ring is measured.

In both constant and falling head tests, the water level in the outer ring is maintained at a constant level to prevent leakage between rings and to force vertical infiltration from the inner ring. Models have shown that falling head and constant head methods give very similar results for

fine textured soils, but the falling head test underestimates infiltration rates for coarse textured soils.

The ASTM standard describes a procedure for measuring the soil infiltration rate with a double-ring infiltrometer for soil with a hydraulic conductivity less than 4 inches per hour. The ASTM standard specifies inner and outer ring diameters of 12 and 24 inches, respectively.

The primary objective of this research was to compare falling head and constant head double ring tests with 6 and 12-inch rings and a constant head test with 12 and 24-inch diameter rings. A secondary objective was to develop a simple device to automatically maintain a constant water level in 6-inch diameter inner ring.

### Measurement methods

An area at the Irrigation Park on the University of Florida campus in Gainesville was used to conduct the double-ring infiltrometer tests. The

# MAKE THE SWITCH TO RED DIAMOND CONDITIONERS



## THE NEW STANDARD IN NATURAL INFIELD CONDITIONERS!

- Promotes Safety
- Professionally Sized Conditioners
- Provides Superior Moisture Management
- Enhances Surface Coloration
- Assist In Proper Field Drainage
- Reduces Rain Delays and Eliminates Rainouts
- 100% Natural Earth Product.



**Mike Bookholder**: Head Groundskeeper Philadelphia Phillies - Citizens Bank Park

"Red Diamond™ is a top quality conditioner. It is very durable and does not break down nearly as fast as other calcined clays that I have used."



**Joe Kennedy III**: Baseball Maintenance Manager Surprise Sports Complex-Surprise, AZ 2005-2006 STMA Complex of the Year

"Red Diamond™ conditioners have proven to be an excellent conditioner. Its consistency and absorption are equal to other conditioners."

**QUANTUM**  
TURF TECHNOLOGIES  
Toll Free (800) 264-5628 • www.meltan.com

Fill in 124 on reader service form or visit <http://oners.hotims.com/9138-124>



# IRRIGATION & DRAINAGE

soil was fine sand, which had been tilled and allowed to settle for several months. Soil textural analysis indicated 92% sand, 4.5% silt, and 3.1% clay.

The three types of tests that were evaluated were: A, the ASTM standard 12-inch (inner) and 24-inch (outer) double-ring infiltrometer under a manually maintained inner ring constant head; B, 12-inch (inner) and 24-inch (outer) infiltration rings under an inner ring constant head with a Mariotte siphon; and C, 12-inch (inner) and 24-inch (outer) infiltration rings under a falling head.

In all three types of tests, the outer ring was maintained manually at a constant head. Maintaining a constant head in the outer ring was not as critical as maintaining constant head in the inner ring to measuring infiltration rates since the purpose of this head is to reduce the leakage of water between rings; therefore, maintaining the head manually was sufficient. The 6 and 12-inch infiltration ring size is typically used in turfgrass systems such as athletic fields for infiltration measurements. In many cases, the falling head test is preferred since less water and time is required to complete a test.

The thin aluminum infiltrometer rings were driven into the ground approximately 6 inches for (A) and 2 inches for (B) and (C). A Mariotte siphon was manufactured from a 4-inch inner diameter Plexiglass pipe cut to a length of 47 inches (see photo). This resulted

Table 1. Statistical analysis of infiltration rates (K) from three types of infiltration tests.

(A) ASTM standard with 12 and 24 inch diameter rings		(B) Constant head with 6 and 12 inch diameter rings		(C) Falling head with 6 and 12 inch diameter rings	
Test no.	K (inch/h)	Test no.	K (inch/h)	Test no.	K (inch/h)
1	4.7	1	3.1	1	6.3
2	5.8	2	8.8	2	2.2
3	4.3	3	6.7	3	5.0
4	6.4	4	7.7	4	3.9
5	----	5	8.2	5	7.3
6	3.4	6	7.5	6	3.1
7	6.0	7	7.9	7	7.7
8	6.0	8	5.9	8	4.7
9	0.8	9	7.6	9	5.0
<b>Mean</b>	<b>4.7</b>	<b>Mean</b>	<b>7.0</b>	<b>Mean</b>	<b>5.0</b>

**GN-1**



**You Can Bet On GN-1™ Hybrid Bermuda  
The Del Mar Thoroughbred Club Does!**



**DEL MAR**

Photo courtesy of Del Mar Thoroughbred Club

305 West Hueneme Road  
Camarillo, CA 93012



**Pacific Sod**  
The Professional's Choice

www.PacificSod.com  
800-942-5296

Fill in 158 on reader service form or visit <http://oners.hotims.com/9138-158>





**THE 6 AND 12-INCH INFILTRATION RING SIZE IS TYPICALLY USED FOR INFILTRATION MEASUREMENTS ON ATHLETIC FIELDS. THE FALLING HEAD TEST IS PREFERRED SINCE LESS WATER AND TIME IS REQUIRED TO COMPLETE A TEST.**

## THE GAME MUST GO ON.

An Airfield is the ultimate sports turf drainage system whether you are playing on natural or artificial turf.



### **Artificial Turf Benefits:**

- Drains remarkably faster
- Reduces installation time
- Reduces G-Max
- Eliminates rubber migration
- Eliminates standing water
- Strong enough for vehicles
- Below entire playing surface
- Air void for heating and cooling
- Allows flushing and sanitizing
- Maintains level playing surface

### **Natural Turf Benefits:**

- Drains remarkably faster
- Reduces installation time
- Reduces irrigation requirements
- Extends playing season
- Eliminates standing water
- Reduces maintenance costs
- Below entire playing surface
- Superior perched water table
- Greater root mass
- Gas circulation through soil



405.359.3775  
airfieldsystems.com

Fill in 133 on reader service form or visit <http://oners.hotims.com/9138-133>

in approximately 3 gallons of water storage, sufficient to keep a constant head in a 6-inch diameter inner ring for more than 4 hours assuming an infiltration rate of 6 inches per hour and for 1 hour assuming an infiltration rate of 27 inches per hour. The 12-inch diameter inner ring used in the ASTM Standard test would require approximately 13 gallons of water to keep a constant head for 1 hour assuming an infiltration rate of 27 inches per hour.

The water level in the outer ring was maintained manually by adjusting a flow valve on a water container (10 gallons) that was used to supply water to the outer ring of the double ring infiltrometer. Alternatively, another Mariotte siphon could be used to maintain a constant water level in the outer ring; however, the water level could be maintained manually with sufficient precision to minimize lateral flow or leakage from the inner ring. Cumulative infiltration and time were recorded, with each test generally lasting 40 to 90 minutes for the constant head test and approximately 20 to 30 minutes for the falling head test. The bulk density and moisture content of the soil were measured adjacent to each test site before each infiltration test was conducted. The infiltration rate was found by regressing the recorded cumulative infiltration and time data.

### **Evaluation**

The table shows the results of the measured infiltration rates from the three different testing methods. Measured infiltration rates on the sandy soil ranged from 0.8 to 8.8 inches per hour and averaged 5.6 inches per hour over all tests. These rates are representative of moderately compacted fine sandy soils. Testing methods (A) and (C) resulted in a significantly lower mean infiltration rate (4.7 and 5.0



inches per hour, respectively) compared to method (B) at 7.0 inches per hour. This difference was expected for the falling head test (C) since the depth of water in the inner ring, one of the components of total head that causes infiltration, decreases during the test. Test (B) had the lowest variability compared to tests (A) and (C). Soil moisture was not different across testing locations, nor was soil bulk density.

It was concluded that the test using a constant head with a double-ring infiltrometer of 6 inches inner diameter and 12 inches outer diameter would be suitable for infiltration research on the sandy soils. These soils have similar infiltration rates to athletic fields built to USGA specifications with mature turf. This allows for infiltration tests to be conducted in areas where the methodology suggested by ASTM would not be suitable due to the volume of water required to maintain a constant head in the larger diameter double-ring infiltrometers can not be easily transported to the site.

The set-up of the double-ring infiltrometer with the Mariotte siphon is an efficient method of conducting a double ring infiltrometer test. The Mariotte siphon automatically maintains a constant head in the inner ring, while the head in the outer ring is maintained manually (a second Mariotte siphon could be used for this). This testing procedure therefore only requires one person to maintain the

head in the outer ring and record the change in water level in the siphon. The volume of water that is needed for this test can also be managed by a single person compared to the large volume of water needed to conduct the ASTM standard test.

## References

1. ASTM. 2003. D3385-03 Standard Test Method for Infiltration Rate of Soils in Field Using Double-Ring Infiltrometer. In Annual Book of ASTM Standards 04.08. Amer. Soc. Testing Materials, West Conshohocken, PA
2. Bouwer, H. 1986. Intake rate: cylinder infiltrometer. p. 825-843. In Methods of Soil Analysis, A. Klute (ed.) ASA Monograph 9. ASA. Madison, WI.
3. Wu, L., L. Pan, M. Robertson, and P. Shouse. 1997. Numerical evaluation of ring infiltrometers under various soil conditions. Soil Sci. 162(11):771-777.

Corresponding Author: Michael D. Dukes, mddukes@ufl.edu

*Michael D. Dukes is an assistant professor at the University of Florida and Grady L. Miller is an associate professor at the University of Florida. Justin H. Gregory is a former graduate research assistant at Florida. ■*

## FIND OUT WHAT WE'RE DOING WHEN WE'RE NOT OUT ON THE GOLF COURSE.



Now the same high quality Par Aide has become known for on courses everywhere is available for the diamond, the field or the court. With rakes, tamps, shovels, brooms, squeegees, spike brushes and more. Built with pride for the grounds you keep with pride. For a catalog and a dealer near you, visit us at [paraidefieldcare.com](http://paraidefieldcare.com) or call 1-888-893-2433.



Par Aide is a registered trademark of Par Aide, Inc.

© Par Aide Products Co., 2006

Fill in 127 on reader service form or visit <http://oners.hotims.com/9138-127>